



ELEVATION ON C.L.

PIPE O/D mm	'A' mm	'C' mm
40	60	900
50	60	900
56	60	900
63	60	900
75	60	900
90	60	900
110	60	1200
125	60	1200
160	55	1500
200	55	1200
250	55	1200
315	55	1200

'A': MINIMUM DIMENSION. IF DOWNPIPE IS REQUIRED TO OFF-SET OUTWITH THE FLANGES OF COLUMN, DIMENSION 'A' TO BE NO LESS DIM 'B'.

'C': MAXIMUM VERTICAL DISTANCE BETWEEN FIXINGS.

THIS DRAWING AND DETAILS CONTAINED WITHIN ARE COPYRIGHT OF HYDROMAX INC. REPRODUCTION OR USE IS PROHIBITED WITHOUT WRITTEN PERMISSION.

Item	Description	Qty	Part No				
1	Backplate (size varies with pipe dia) BZP	-	-				
2	Tek Screw (self drilling/tapping)	-	-				



Drawn By	Date
W Jackson	03/02/06
Scale	Rev
n.t.s.	00
Drawing No	
AD512	

Drawing Title  
 TYPICAL FIXING DETAIL; HDPE DOWNPIPE TO MAIN STEELWORK (BACKPLATE)